



KEY FEATURES

- ☆ **Hytrel Coating**
Protects users and sensitive underground utilities
Bonus: Lasts 2-3 times longer than previous coating



- ☆ **Rubber Boot**
Provides a smooth rotation



- ☆ **Tungsten Carbide Nozzle Tip and Seat**
Materials proven to outlast ceramic nozzles



- ☆ **Inlet Connection**
1/2" FNPT



- ☆ **Inlet Screen**
Protects nozzle from contaminants



Easily rebuild the Ripsaw in just 10 minutes with our field repair kits.



REPAIR KIT



DOME INLET
SCREENS

10 Pack



Part Number: 20019939

NOZZLE SIZE	RIPSAW HD NOZZLE PART NUMBER	REPAIR KIT PART NUMBER	FLOW RATE CHART (GPM)					
			@1,000 PSI (70 Bar)	@1,500 PSI (103 Bar)	@2,000 PSI (138 Bar)	@2,500 PSI (172 Bar)	@3,000 PSI (207 Bar)	@3,200 PSI (221 Bar)
3.0	20022380	20022328	1.5 GPM (5.7 LPM)	1.8 GPM (6.8 LPM)	2.1 GPM (7.9 LPM)	2.4 GPM (9.1 LPM)	2.6 GPM (9.8 LPM)	2.7 GPM (10.2 LPM)
4.0	20022381	20022329	2.0 GPM (7.6 LPM)	2.4 GPM (9.1 LPM)	2.8 GPM (10.6 LPM)	3.2 GPM (12.1 LPM)	3.5 GPM (13.2 LPM)	3.6 GPM (13.6 LPM)
5.0	20022382	20022330	2.5 GPM (9.5 LPM)	3.1 GPM (11.7 LPM)	3.5 GPM (13.2 LPM)	4.0 GPM (15.1 LPM)	4.3 GPM (16.3 LPM)	4.5 GPM (17.0 LPM)
6.0	20022383	20022331	3.0 GPM (11.4 LPM)	3.7 GPM (14.0 LPM)	4.2 GPM (15.9 LPM)	4.7 GPM (17.8 LPM)	5.2 GPM (19.7 LPM)	5.4 GPM (20.4 LPM)
8.0	20022384	20022332	4.0 GPM (15.1 LPM)	4.9 GPM (18.5 LPM)	5.7 GPM (21.6 LPM)	6.3 GPM (23.8 LPM)	6.9 GPM (26.1 LPM)	7.2 GPM (27.3 LPM)
10.0	20022385	20022333	5.0 GPM (18.9 LPM)	6.1 GPM (23.1 LPM)	7.1 GPM (26.9 LPM)	7.9 GPM (29.9 LPM)	8.7 GPM (32.9 LPM)	8.9 GPM (33.7 LPM)
12.0	20022386	20022334	6.0 GPM (22.7 LPM)	7.3 GPM (27.6 LPM)	8.5 GPM (32.2 LPM)	9.5 GPM (36.0 LPM)	10.4 GPM (39.4 LPM)	10.7 GPM (40.5 LPM)



OUTFIT YOUR RIG

Hydro-Excavation or Municipal-
focused demo boxes are available
to fully outfit your rig. Email us for
more info.

hello@hydraflexinc.com



FIND A HYDRA-FLEX
DEALER IN YOUR AREA